

MULCHER FOR SKID STEERS

DML/SSL - DML/SSL/VT



from 40 to 70 HP



Ø 5 in max

FORESTRY MULCHER WITH FIXED BLADE ROTOR FOR SKID STEERS.

The DML/SSL is the smallest of the FAE fixed tooth mulchers designed and manufactured to be utilized with skid steers up to 70 HP. The heavy duty construction of the frame makes it a long term investment, while the special design of the fixed tooth rotor allows a neat cut of the material and guarantees maximum reliability and high performance. The automatic variable displacement hydraulic motor with mechanical adjustment makes it the ideal solution for skid steers that are not equipped with a high flow system.



STANDARD EQUIPMENT
Anti dust machine body
Belt transmission
17/34cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (DML/SSL) - (13 - 26 GPM)
55/38cc variable torque hydraulic piston motor (DML/SSL/VT) - (16 - 30 GPM)
Hydraulic hoses
Hydraulic rear hood
Welded counter blade

Working pressure control gauge
Pushing frame
Diverter valve (plug & play)
Motor integrated into the frame
OPTIONS
Customized setting hydraulic motor (DML/SSL/VT)
32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (DML/SSL) - (24 - 34 GPM)
Hydraulic couplers
Electrical connector



External pressure control Gauge

VT motor

Adjustable motor to obtain the maximum performance out of any skid steer

Diverter valve to control hood cylinder

to control the opening and closing of the hydraulic door

Steel counter-blades

helps mulch material into a smaller final size



MODEL	Engine (HP)		Flow rate (gal/min)		Pressure (PSI)		Working width (in)	Total width (in)	Weight (lbs)	Max shredding diameter (in)	No. blades type E
	min	max	min	max	min	max					
DML/SSL 125	40	70	13	34	2600	3600	49	60	1522	5	30
DML/SSL 150	40	70	13	34	2600	3600	59	69	1656	5	36
DML/SSL 175	40	70	13	34	2600	3600	68	79	1950	5	42
DML/SSL/VT 125*	40	70	16	30	2600	5000	49	60	1522	5	30
DML/SSL/VT 150*	40	70	16	30	2600	5000	59	69	1656	5	36
DML/SSL/VT 175*	40	70	16	30	2600	5000	68	79	1950	5	42

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.

*Variable displacement hydraulic motor.